

Progress-M/MF (Pg)

Material: Messing vernickelt
Dichteinsatz: TPE
O-Ring: NBR
Einsatztemperatur: -40°C bis 100°C
Schutzart: IP 68

Material: brass, nickel-plated
Sealing insert: TPE
O-ring: NBR
Temperature range: -40°C to 100°C
Protection type: IP 68



101.04
101.24

Gewinde Entry Thread AG				H mm	Gew. kurz / Thread short		Gew. lang / Thread long	
					GL mm	HUGRO No.	GL mm	HUGRO No.
Pg 9	2,0 - 3,0	2	18	22	6	101.09302.04	10	101.09302.24
Pg 9	2,5 - 4,0	2	18	22	6	101.09402.04	10	101.09402.24
Pg 9	3,5 - 5,0	2	18	22	6	101.09502.04	10	101.09502.24
Pg 11	3,5 - 5,0	2	21	21	6	101.11502.04	10	101.11502.24
Pg 11	3,5 - 5,0	3	21	21	6	101.11503.04	10	101.11503.24
Pg 11	4,5 - 6,0	2	21	21	6	101.11602.04	10	101.11602.24
Pg 11	5,5 - 7,5	2	24	23	6	101.11752.04	10	101.11752.24
Pg 13,5	3,5 - 5,0	2	24	23	6	101.13502.04	10	101.13502.24
Pg 13,5	3,5 - 5,0	3	24	23	6	101.13503.04	10	101.13503.24
Pg 13,5	3,5 - 5,0	4	24	23	6	101.13504.04	10	101.13504.24
Pg 13,5	4,5 - 6,0	2	24	23	6	101.13602.04	10	101.13602.24
Pg 13,5	4,5 - 6,0	3	24	23	6	101.13603.04	10	101.13603.24
Pg 13,5	4,5 - 6,0	4	24	23	6	101.13604.04	10	101.13604.24
Pg 13,5	5,2 - 6,5	3	24	23	6	101.13653.04	10	101.13653.24
Pg 13,5	5,5 - 7,5	2	24	23	6	101.13752.04	10	101.13752.24
Pg 16	3,5 - 5,0	2	24	23	6	101.16502.04	10	101.16502.24
Pg 16	3,5 - 5,0	3	24	23	6	101.16503.04	10	101.16503.24
Pg 16	3,5 - 5,0	4	24	23	6	101.16504.04	10	101.16504.24
Pg 16	4,5 - 6,0	2	24	23	6	101.16602.04	10	101.16602.24
Pg 16	4,5 - 6,0	3	24	23	6	101.16603.04	10	101.16603.24
Pg 16	4,5 - 6,0	4	24	23	6	101.16604.04	10	101.16604.24
Pg 16	5,0 - 7,0	3	30	28	6	101.16703.04	10	101.16703.24
Pg 16	5,5 - 7,0	4	30	28	6	101.16704.04	10	101.16704.24
Pg 16	5,5 - 7,5	2	24	23	6	101.16752.04	10	101.16752.24
Pg 16	6,7 - 9,0	2	30	28	6	101.16902.04	10	101.16902.24
Pg 21	4,8 - 6,0	6	30	28	7,5	101.21606.04	12	101.21606.24
Pg 21	5,0 - 7,0	2	30	28	7,5	101.21702.04	12	101.21702.24
Pg 21	5,5 - 7,0	3	30	28	7,5	101.21703.04	12	101.21703.24
Pg 21	5,5 - 7,0	4	30	28	7,5	101.21704.04	12	101.21704.24
Pg 21	5,8 - 7,0	6	36	28	7,5	101.21706.04	12	101.21706.24
Pg 21	6,7 - 9,0	2	30	28	7,5	101.21902.04	12	101.21902.24
Pg 21	6,8 - 9,0	3	30	28	7,5	101.21903.04	12	101.21903.24
Pg 21	7,0 - 9,0	4	36	28	7,5	101.21904.04	12	101.21904.24
Pg 21	7,7 - 10,0	2	30	28	7,5	101.21102.04	12	101.21102.24
Pg 21	8,5 - 10,5	3	36	28	7,5	101.21103.04	12	101.21103.24
Pg 21	9,0 - 11,5	2	36	28	7,5	101.21112.04	12	101.21112.24
Pg 29	7,5 - 9,0	3	38	28	8	101.29903.04	12	101.29903.24

