




Uni-Dicht / MF (Pg)


Material: Messing vernickelt  
Dichteinsatz: TPE  
O-Ring: NBR  
Einsatztemperatur: -40°C bis 130°C  
Schutzart: IP 65

Material: brass, nickel-plated  
Sealing insert: TPE  
O-ring: NBR  
Temperature range: -40°C up to 130°C  
Protection type: IP 65



106.14

Gewinde Entry Thread AG	 mm	H mm	GL mm	 mm	HUGRO No.	 mm	HUGRO No.
Pg 9	17	19	6	2 x 1,2	106.09122.14	4 x 1,4	106.09144.14
Pg 9	17	19	6	2 x 3	106.09302.14	3 x 3	106.09303.14
Pg 9	17	19	6	4 x 3	106.09304.14	2 x 4	106.09402.14
Pg 11	20	20	6			4 x 1,5	106.11154.14
Pg 11	20	20	6	7 x 1,5	106.11157.14	9 x 1,5	106.11159.14
Pg 11	20	20	6	6 x 2	106.11206.14	2 x 2,3	106.11232.14
Pg 11	20	20	6	6 x 2,5	106.11256.14	2 x 3	106.11302.14
Pg 11	20	20	6	3 x 3	106.11303.14	5 x 3,5	106.11355.14
Pg 11	20	20	6	2 x 4	106.11402.14	3 x 4	106.11403.14
Pg 11	20	20	6	2 x 5	106.11502.14	2 x 6	106.11602.14
Pg 13,5	22	20	6,5	8 x 1,5	106.13158.14	3 x 2	106.13203.14
Pg 13,5	22	20	6,5	10 x 2	106.13210.14	2 x 3	106.13302.14
Pg 13,5	22	20	6,5	3 x 3	106.13303.14	4 x 3	106.13304.14
Pg 13,5	22	20	6,5	6 x 3,5	106.13356.14	3 x 4	106.13403.14
Pg 13,5	22	20	6,5	2 x 5	106.13502.14	2 x 6	106.13602.14
Pg 16	24	20	6,5	7 x 2	106.16207.14	3 x 3	106.16303.14
Pg 16	24	20	6,5	9 x 3	106.16309.14	2 x 4	106.16402.14
Pg 16	24	20	6,5	4 x 4	106.16404.14	6 x 4	106.16406.14
Pg 16	24	20	6,5	2 x 6	106.16602.14	4 x 6	106.16604.14
Pg 16	24	20	6,5	3 x 7	106.16703.14	2 x 8	106.16802.14
Pg 21	30	25	7	21 x 2	106.21221.14	8 x 3	106.21308.14
Pg 21	30	25	7	6 x 4	106.21406.14	8 x 4	106.21408.14
Pg 21	30	25	7	2 x 4,5	106.21452.14	4 x 5	106.21504.14
Pg 21	30	25	7	6 x 5	106.21506.14	8 x 5	106.21508.14
Pg 21	30	25	7	4 x 6	106.21604.14	4 x 6,5	106.21654.14
Pg 21	30	25	7	6 x 6,5	106.21656.14	3 x 7	106.21703.14
Pg 21	30	25	7	2 x 8	106.21802.14	4 x 8	106.21804.14
Pg 21	30	25	7	2 x 9	106.21902.14	3 x 9	106.21903.14
Pg 29	40	27	8	12 x 5,3	106.29512.14	6 x 6	106.29606.14
Pg 29	40	27	8	10 x 6	106.29610.14	7 x 7	106.29707.14
Pg 29	40	27	8	5 x 8	106.29805.14	6 x 8	106.29806.14
Pg 29	40	27	8	4 x 9	106.29904.14	5 x 9	106.29905.14
Pg 29	40	27	8	4 x 10	106.29104.14	5 x 10	106.29105.14
Pg 29	40	27	8	2 x 11	106.29112.14	3 x 11	106.29113.14
Pg 29	40	27	8	2 x 13	106.29132.14		
Pg 36	50	32	8,5	15 x 5	106.36515.14	13 x 7	106.36713.14
Pg 36	50	32	8,5	8 x 8	106.36808.14	11 x 8	106.36811.14
Pg 36	50	32	8,5	7 x 9	106.36907.14	8 x 9	106.36908.14
Pg 36	50	32	8,5	3 x 10	106.36103.14	4 x 11,5	106.36114.14
Pg 36	50	32	8,5	5 x 11,5	106.36115.14	4 x 13	106.36134.14
Pg 36	50	32	8,5	2 x 15	106.36152.14		
Pg 48	65	35	10	8 x 10	106.48108.14	4 x 12	106.48124.14
Pg 48	65	35	10	8 x 12	106.48128.14	4 x 16	106.48164.14
Pg 48	65	35	10	3 x 18	106.48183.14		



**Auf Anfrage:**

- weitere Ausführungen mit unterschiedlichen Bohrungen
- Bolzen zum Verschließen nicht gebrauchter Bohrungen siehe Zubehör - Serie 683

**On request:**

- further versions with different holes
- Plugs for closing of not used holes see accessories - series 683