

**WADI-PL**

Material: PA 6  
 Farbe: grau / schwarz  
 Dichteinsatz: CR  
 Einsatztemperatur: -40°C bis 100°C  
 Schutzart: IP 68

Material: PA 6  
 Colour: grey / black  
 Sealing insert: CR  
 Temperature range: -40°C to 100°C  
 Protection type: IP 68

**178.SKG 178.SKS**  
**178.SLG 178.SLS**

Internationale Zulassungen vorhanden

International approvals available

Gewinde Entry Thread AG			H mm	GL mm	grau / grey RAL 7035 HUGRO No.	schwarz / black RAL 9005 HUGRO No.
-------------------------------	---	---	---------	----------	--------------------------------------	--

kurzes Anschlussgewinde / short entry thread						
M 12 x 1,5	1,5 - 5	15	24	8	178.1505.SKG	178.1505.SKS
M 12 x 1,5	2,5 - 6,5	15	24	8	178.1507.SKG	178.1507.SKS
M 16 x 1,5	1,5 - 6	19	27	10	178.1706.SKG	178.1706.SKS
M 16 x 1,5	2,5 - 8	19	27	10	178.1708.SKG	178.1708.SKS
M 16 x 1,5	2 - 7	22	29	10	178.1707.SKG	178.1707.SKS
M 16 x 1,5	3,5 - 10	22	29	10	178.1710.SKG	178.1710.SKS
M 20 x 1,5	3 - 9	24	30	10	178.2009.SKG	178.2009.SKS
M 20 x 1,5	5 - 12	24	30	10	178.2012.SKG	178.2012.SKS
M 20 x 1,5	7 - 14	27	33	10	178.2014.SKG	178.2014.SKS
M 25 x 1,5	5 - 12	27	35	10	178.2512.SKG	178.2512.SKS
M 25 x 1,5	7 - 14	27	35	10	178.2514.SKG	178.2514.SKS
M 25 x 1,5	7 - 16	33	39	10	178.2516.SKG	178.2516.SKS
M 25 x 1,5	9 - 18	33	39	10	178.2518.SKG	178.2518.SKS
M 32 x 1,5	11 - 21	42	42	10	178.3221.SKG	178.3221.SKS
M 32 x 1,5	14 - 25	42	42	10	178.3225.SKG	178.3225.SKS
M 40 x 1,5	13 - 26	53	52	10	178.4026.SKG	178.4026.SKS
M 40 x 1,5	18 - 32	53	52	10	178.4032.SKG	178.4032.SKS
M 50 x 1,5	17 - 31	60	55	12	178.5031.SKG	178.5031.SKS
M 50 x 1,5	24 - 38,5	60	55	12	178.5038.SKG	178.5038.SKS
M 63 x 1,5	26 - 39	70	56	12	178.6339.SKG	178.6339.SKS
M 63 x 1,5	35 - 48	70	56	12	178.6348.SKG	178.6348.SKS

langes Anschlussgewinde / long entry thread						
M 12 x 1,5	1,5 - 5	15	24	15	178.1505.SLG	178.1505.SLS
M 12 x 1,5	2,5 - 6,5	15	24	15	178.1507.SLG	178.1507.SLS
M 16 x 1,5	1,5 - 6	19	27	15	178.1706.SLG	178.1706.SLS
M 16 x 1,5	2,5 - 8	19	27	15	178.1708.SLG	178.1708.SLS
M 16 x 1,5	2 - 7	22	29	15	178.1707.SLG	178.1707.SLS
M 16 x 1,5	3,5 - 10	22	29	15	178.1710.SLG	178.1710.SLS
M 20 x 1,5	3 - 9	24	30	15	178.2009.SLG	178.2009.SLS
M 20 x 1,5	5 - 12	24	30	15	178.2012.SLG	178.2012.SLS
M 20 x 1,5	7 - 14	27	33	15	178.2014.SLG	178.2014.SLS
M 25 x 1,5	5 - 12	27	35	15	178.2512.SLG	178.2512.SLS
M 25 x 1,5	7 - 14	27	35	15	178.2514.SLG	178.2514.SLS
M 25 x 1,5	7 - 6	33	39	15	178.2516.SLG	178.2516.SLS
M 25 x 1,5	9 - 18	33	39	15	178.2518.SLG	178.2518.SLS
M 32 x 1,5	11 - 21	42	42	15	178.3221.SLG	178.3221.SLS
M 32 x 1,5	14 - 25	42	42	15	178.3225.SLG	178.3225.SLS
M 40 x 1,5	13 - 26	53	52	16	178.4026.SLG	178.4026.SLS
M 40 x 1,5	18 - 32	53	52	16	178.4032.SLG	178.4032.SLS
M 50 x 1,5	17 - 31	60	55	16	178.5031.SLG	178.5031.SLS
M 50 x 1,5	24 - 38,5	60	55	16	178.5038.SLG	178.5038.SLS
M 63 x 1,5	26 - 39	70	56	16	178.6339.SLG	178.6339.SLS
M 63 x 1,5	35 - 48	70	56	16	178.6348.SLG	178.6348.SLS

**Auf Anfrage:** in dunkelgrau (RAL 7001)      **On request:** in dark grey (RAL 7001)

