

**Progress-P/MF**

Material: PA, glasfaserverstärkt  
 Farbe: grau (RAL 7035)  
 Dichteinsatz: TPE  
 Einsatztemperatur: -20°C bis 100°C  
 Schutzart: IP 68




Material: PA (nylon), glass-fibre reinforced  
 Colour: grey (RAL 7035)  
 Sealing insert: TPE  
 Temperature range: -20°C to 100°C  
 Protection type: IP 68

**180.40**

Weitere internationale Zulassungen vorhanden

Further international approvals available



Gewinde Entry Thread AG	 mm		 mm	H mm	GL mm	HUGRO No.
M 16 x 1,5	2,0 - 3,0	2	21	26	12	180.17302.40
M 16 x 1,5	2,5 - 4,0	2	21	26	12	180.17402.40
M 16 x 1,5	3,5 - 5,0	2	21	26	12	180.17502.40
M 20 x 1,5	3,5 - 5,0	2	27	28	13	180.20502.40
M 20 x 1,5	3,5 - 5,0	3	27	28	13	180.20503.40
M 20 x 1,5	3,5 - 5,0	4	27	28	13	180.20504.40
M 20 x 1,5	4,5 - 6,0	2	27	28	13	180.20602.40
M 20 x 1,5	4,5 - 6,0	3	27	28	13	180.20603.40
M 20 x 1,5	4,5 - 6,0	4	27	28	13	180.20604.40
M 20 x 1,5	5,2 - 6,5	3	27	28	13	180.20653.40
M 20 x 1,5	5,5 - 7,5	2	27	28	13	180.20752.40
M 25 x 1,5	4,8 - 6,0	6	34	33	13	180.25606.40
M 25 x 1,5	5,0 - 7,0	2	34	33	13	180.25702.40
M 25 x 1,5	5,5 - 7,0	3	34	33	13	180.25703.40
M 25 x 1,5	5,5 - 7,0	4	34	33	13	180.25704.40
M 25 x 1,5	6,7 - 9,0	2	34	33	13	180.25902.40
M 25 x 1,5	6,8 - 9,0	3	34	33	13	180.25903.40
M 25 x 1,5	7,7 - 10,0	2	34	33	13	180.25102.40
M 32 x 1,5	5,8 - 7,0	6	41	35	15	180.32706.40
M 32 x 1,5	7,0 - 9,0	3	41	35	15	180.32903.40
M 32 x 1,5	7,0 - 9,0	4	41	35	15	180.32904.40
M 32 x 1,5	8,5 - 10,5	3	41	35	15	180.32103.40
M 32 x 1,5	9,0 - 11,5	2	41	35	15	180.32112.40

Weitere Ausführungen und andere Farben auf Anfrage

Further versions and other colours are available on request

