

Progress-EMV / EX

Material: Messing vernickelt
 Dichteinsatz: TPE
 O-Ring: FPM
 Einsatztemperatur: -60°C bis 100°C
 Schutzart: IP 66 / IP 68 (bis 10 bar)

Material: brass, nickel-plated
 Sealing insert: TPE
 O-ring: FPM
 Temperature range: -60°C to 100°C
 Protection type: IP 66 / IP 68 (up to 10 bar)



107.10

Zertifikate: SEV 15 ATEX 0152 X
 IECEx SEV 15.0019 X

Certificates: SEV 15 ATEX 0152 X
 IECEx SEV 15.0019 X




Weitere internationale Zulassungen vorhanden

Further international approvals available



II 2G Ex eb IIC Gb
 II 2D Ex tb IIIC Db

Gewinde Entry Thread AG	$\varnothing k$ mm	$\varnothing M$ mm	H mm	GL mm	Progress MS EMV EX	HUGRO No.
M 8 x 1,25	2,5 - 3,5	11	14	5	EX1080.08.035	107.0803.10
M 8 x 1,25	3 - 4	11	14	5	EX1080.08.040	107.0804.10
M 10 x 1,5	3 - 4	13	15	5	EX1080.10.040	107.1004.10
M 10 x 1,5	4 - 6	13	15	5	EX1080.10.060	107.1006.10
M 12 x 1,5	4,5 - 6	15	17	5	EX1080.12.060	107.1506.10
M 12 x 1,5	6 - 7,5	15	17	5	EX1080.12.075	107.1507.10
M 16 x 1,5	6 - 8	18	20	5	EX1080.17.080	107.1708.10
M 16 x 1,5	8 - 10	18	22	5	EX1080.17.100	107.1710.10
M 20 x 1,5	8 - 11	24	21	6	EX1080.20.110	107.2011.10
M 20 x 1,5	12,5 - 14	24	23	6	EX1080.20.140	107.2014.10
M 25 x 1,5	13 - 16	30	25	7	EX1080.25.160	107.2516.10
M 25 x 1,5	17 - 19	30	28	7	EX1080.25.190	107.2519.10
M 32 x 1,5	17 - 21	36	29	8	EX1080.32.210	107.3221.10
M 40 x 1,5	23 - 28,5	46	31	8	EX1080.40.285	107.4028.10
Pg 7	4,5 - 6	15	17	6	EX1080.07.060	107.0706.10
Pg 7	6 - 7,5	15	17	6	EX1080.07.075	107.0707.10
Pg 9	6 - 8	18	20	6	EX1080.09.080	107.0908.10
Pg 9	8 - 10	18	22	6	EX1080.09.100	107.0910.10
Pg 11	5,5 - 8,5	21	21	6	EX1080.11.085	107.1108.10
Pg 11	8,5 - 12	21	21	6	EX1080.11.120	107.1112.10
Pg 13,5	8 - 11	24	21	6	EX1080.13.110	107.1311.10
Pg 13,5	12,5 - 14	24	23	6	EX1080.13.140	107.1314.10
Pg 16	8 - 11	24	21	6	EX1080.16.110	107.1611.10
Pg 16	12,5 - 14	24	23	6	EX1080.16.140	107.1614.10
Pg 21	13 - 16	30	25	7,5	EX1080.21.160	107.2116.10
Pg 21	17 - 19	30	28	7,5	EX1080.21.190	107.2119.10
Pg 29	19 - 23	38	29	8	EX1080.29.230	107.2923.10
Pg 29	23 - 25,5	38	29	8	EX1080.29.255	107.2925.10
Pg 36	25 - 30,5	50	32	8	EX1080.36.305	107.3630.10



Eigenschaften:

- einfache, schnelle und sichere Montage
- sehr guter Schirmkontakt 360° über Kontakthülse
- konstante Kontaktqualität mit kleinster Kopplungsimpedanz

Characteristics:

- easy, fast and safe to install
- efficient 360° shield contact with contact socket
- constant contact quality with low impedance

