

Progress-EMV easyConnect / ZE-EX

Material: Messing vernickelt
Schrauben: rostfreier Stahl A2
Dichteinsatz: TPE
O-Ring: FPM
Einsatztemperatur: -60°C bis 100°C
Schutzart: IP 66 / IP 68

Material: brass, nickel-plated
Screws: stainless steel A2
Sealing insert: TPE
O-ring: FPM
Temperature range: -60°C to 100°C
Protection type: IP 66 / IP 68

Zertifikate: SEV 15 ATEX 0151
IECEX SEV 15.0018
SEV 15 ATEX 0152 X*
IECEX SEV 15.0019 X*



Certificates: SEV 15 ATEX 0151
IECEX SEV 15.0018
SEV 15 ATEX 0152 X*
IECEX SEV 15.0019 X*



107.ZE



II 2G Ex eb IIC Gb
II 2D Ex tb IIIC Db

Gewinde Entry Thread AG			H mm	GL mm	Progress MS EMV easyCONNECT KB	HUGRO No.
M 12 x 1,5	5 - 6,5	15 / 16	31	5	EX1803.83.12.065	107.1506.10.ZE *
M 16 x 1,5	6 - 10	18 / 19	33	5	EX1803.83.17	107.1702.10.ZE
M 20 x 1,5	8 - 15	24	35	6	EX1803.83.20	107.2002.10.ZE
M 25 x 1,5	12,5 - 20,5	30	40	7	EX1803.83.25	107.2502.10.ZE
M 32 x 1,5	17 - 25,5	36	45	8	EX1803.83.32	107.3202.10.ZE
M 40 x 1,5	24 - 33	46	51	8	EX1803.83.40	107.4002.10.ZE
M 50 x 1,5	33 - 42	55	57	9	EX1803.83.50	107.5002.10.ZE
M 63 x 1,5	40 - 52	70	60	10	EX1803.83.63	107.6302.10.ZE
langes Anschlussgewinde / long entry thread						
M 12 x 1,5	5 - 6,5	15 / 16	31	10	EX1813.83.12.065	107.1506.30.ZE *
M 16 x 1,5	6 - 10	18 / 19	33	10	EX1813.83.17	107.1702.30.ZE
M 20 x 1,5	8 - 15	24	35	10	EX1813.83.20	107.2002.30.ZE
M 25 x 1,5	12,5 - 20,5	30	40	11	EX1813.83.25	107.2502.30.ZE
M 32 x 1,5	17 - 25,5	36	45	13	EX1813.83.32	107.3202.30.ZE
M 40 x 1,5	24 - 33	46	51	13	EX1813.83.40	107.4002.30.ZE
M 50 x 1,5	33 - 42	55	57	14	EX1813.83.50	107.5002.30.ZE
M 63 x 1,5	40 - 52	70	60	14	EX1813.83.63	107.6302.30.ZE

