

Progress-EMV/ZE-EX

Material: Messing vernickelt
Schrauben: rostfreier Stahl A2
Dichteinsatz: TPE
O-Ring: FPM
Einsatztemperatur: -60°C bis 100°C
Schutzart: IP 66/IP 68 (bis 10 bar)

Material: brass, nickel-plated
Screws: stainless steel A2
Sealing insert: TPE
O-ring: FPM
Temperature range: -60°C to 100°C
Protection type: IP 66/IP 68 (up to 10 bar)



148.10

Zertifikate: SEV 15 ATEX 0151
IECEX SEV 15.0018
SEV 15 ATEX 0152 X*
IECEX SEV 15.0019 X*

Certificates: SEV 15 ATEX 0151
IECEX SEV 15.0018
SEV 15 ATEX 0152 X*
IECEX SEV 15.0019 X*




II 2G Ex eb IIC Gb
II 2D Ex tb IIIC Db

Weitere internationale Zulassungen vorhanden

Further international approvals available

Gewinde Entry Thread AG	mm	mm	H mm	GL mm	Progress MS EMV KB EX	HUGRO No.
M 12 x 1,5	4,5 - 6	15/16	26	5	EX1803.80.12.060	148.1506.10 *
M 12 x 1,5	6 - 7,5	15/16	26	5	EX1803.80.12.075	148.1507.10 *
M 16 x 1,5	6 - 8	18/19	30	5	EX1803.80.17.080	148.1708.10
M 16 x 1,5	8 - 10	18/19	30	5	EX1803.80.17.100	148.1710.10
M 20 x 1,5	8 - 11	24	31	6	EX1803.80.20.110	148.2011.10
M 20 x 1,5	11 - 14	24	31	6	EX1803.80.20.140	148.2014.10
M 25 x 1,5	13 - 16	30	35	7	EX1803.80.25.160	148.2516.10
M 25 x 1,5	16 - 19	30	35	7	EX1803.80.25.190	148.2519.10
M 32 x 1,5	18 - 21	36	40	8	EX1803.80.32.210	148.3221.10
M 32 x 1,5	21 - 25	36	40	8	EX1803.80.32.250	148.3225.10
M 40 x 1,5	24 - 28,5	46	44	8	EX1803.80.40.285	148.4028.10
M 40 x 1,5	28,5 - 32	46	44	8	EX1803.80.40.320	148.4032.10
M 50 x 1,5	33 - 37	55	49	9	EX1803.80.50.370	148.5037.10
M 50 x 1,5	37 - 41	55	49	9	EX1803.80.50.410	148.5041.10
M 63 x 1,5	40 - 46	70	55	10	EX1803.80.63.460	148.6346.10
M 63 x 1,5	46 - 50	70	55	10	EX1803.80.63.500	148.6350.10
Pg 7	4,5 - 6	15/16	26	6	EX1803.80.07.060	148.0706.10 *
Pg 7	6 - 7,5	15/16	26	6	EX1803.80.07.075	148.0707.10 *
Pg 9	6 - 8	18/19	30	6	EX1803.80.09.080	148.0908.10
Pg 9	8 - 10	18/19	30	6	EX1803.80.09.100	148.0910.10
Pg 11	5,5 - 8,5	21	31	6	EX1803.80.11.085	148.1108.10
Pg 11	8,5 - 12	21	31	6	EX1803.80.11.120	148.1112.10
Pg 13,5	8 - 11	24	31	6	EX1803.80.13.110	148.1311.10
Pg 13,5	11 - 14	24	31	6	EX1803.80.13.140	148.1314.10
Pg 16	8 - 11	24	31	6	EX1803.80.16.110	148.1611.10
Pg 16	11 - 14	24	31	6	EX1803.80.16.140	148.1614.10
Pg 21	13 - 16	30	35	7,5	EX1803.80.21.160	148.2116.10
Pg 21	16 - 19	30	35	7,5	EX1803.80.21.190	148.2119.10
Pg 29	19 - 23	38	40	8	EX1803.80.29.230	148.2923.10
Pg 29	23 - 25,5	38	40	8	EX1803.80.29.255	148.2925.10
Pg 36	25 - 30,5	50	47	8	EX1803.80.36.305	148.3630.10
Pg 36	30,5 - 35	50	47	8	EX1803.80.36.350	148.3635.10
Pg 42	33 - 37	55	49	10	EX1803.80.42.370	148.4237.10
Pg 42	37 - 41	55	49	10	EX1803.80.42.410	148.4241.10
Pg 48	39 - 43	65	51	11	EX1803.80.48.430	148.4843.10
Pg 48	43 - 46,5	65	51	11	EX1803.80.48.465	148.4846.10



Eigenschaften:

- einfache, schnelle und sichere Montage
- sehr guter Schirmkontakt 360° über Kontakthülse
- konstante Kontaktqualität mit kleinster Kopplungsimpedanz

Characteristics:

- easy, fast and safe to install
- efficient 360° shield contact with contact socket
- constant contact quality with low impedances