

WAZU-M/EX

Material: Messing vernickelt
Klemmeinsatz: PA, VO nach UL 94
Dichtung: NBR
O-Ring: NBR
Einsatztemperatur: -20 °C bis 95 °C
Schutzart: IP 68 - 10 bar / 30 min
IP 69 K

Material: brass, nickel-plated
Clamping insert: PA (nylon), VO acc. to UL 94
Sealing insert: NBR
O-ring: NBR
Temperature range: -20 °C to 95 °C
Protection type: IP 68 - 10 bar / 30 min
IP 69 K

Zertifikate: DMT 03 ATEX E 051 X
IECEx BVS 07.0019 X

Certificates: DMT 03 ATEX E 051 X
IECEx BVS 07.0019 X



154.10
154.30



II 1D Ex ta IIIC Da
II 2G Ex eb IIC Gb



Weitere internationale Zulassungen vorhanden

Further international approvals available

Gewinde Entry Thread AG			H mm	GL mm	HSK-M-Ex	HUGRO No.
kurzes Anschlussgewinde / short entry thread						
M 12 x 1,5	2 - 5	14	19	6,5	1.610.1200.51	154.1505.10
M 12 x 1,5	3 - 6,5	14	19	6,5	1.610.1200.50	154.1507.10
M 16 x 1,5	2 - 6	19/17	21	6	1.610.1600.51	154.1706.10
M 16 x 1,5	4 - 8	19/17	21	6	1.610.1600.50	154.1708.10
M 16 x 1,5	5 - 10	20	22	6	1.610.1611.50	154.1710.10
M 20 x 1,5	5 - 9	22	23	6	1.610.2000.51	154.2009.10
M 20 x 1,5	6 - 12	22	23	6	1.610.2000.50	154.2012.10
M 20 x 1,5	10 - 14	24	24	6	1.610.2016.50	154.2014.10
M 25 x 1,5	10 - 16	30	25	7	1.610.2500.51	154.2516.10
M 25 x 1,5	14 - 18	30	25	7	1.610.2500.50	154.2518.10
M 32 x 1,5	13 - 20	40	31	8	1.610.3200.51	154.3220.10
M 32 x 1,5	20 - 25	40	31	8	1.610.3200.50	154.3225.10
M 40 x 1,5	20 - 26	50	37	8	1.610.4000.51	154.4026.10
M 40 x 1,5	22 - 32	50	37	8	1.610.4000.50	154.4032.10
M 50 x 1,5	25 - 31	57	37	9	1.610.5000.51	154.5031.10
M 50 x 1,5	32 - 38	57	37	9	1.610.5000.50	154.5038.10
M 63 x 1,5	29 - 35	68/64	38	10	1.610.6300.51	154.6335.10
M 63 x 1,5	37 - 44	68/64	38	10	1.610.6300.50	154.6344.10
langes Anschlussgewinde / long entry thread						
M 12 x 1,5	2 - 5	14	19	10	1.610.1200.31	154.1505.30
M 12 x 1,5	3 - 6,5	14	19	10	1.610.1200.30	154.1507.30
M 16 x 1,5	2 - 6	19/17	21	10	1.610.1600.31	154.1706.30
M 16 x 1,5	4 - 8	19/17	21	10	1.610.1600.30	154.1708.30
M 16 x 1,5	5 - 10	20	22	10	1.610.1611.30	154.1710.30
M 20 x 1,5	5 - 9	22	23	10	1.610.2000.31	154.2009.30
M 20 x 1,5	6 - 12	22	23	10	1.610.2000.30	154.2012.30
M 20 x 1,5	10 - 14	24	24	10	1.610.2016.30	154.2014.30
M 25 x 1,5	10 - 16	30	25	12	1.610.2500.31	154.2516.30
M 25 x 1,5	14 - 18	30	25	12	1.610.2500.30	154.2518.30
M 32 x 1,5	13 - 20	40	31	12	1.610.3200.31	154.3220.30
M 32 x 1,5	20 - 25	40	31	12	1.610.3200.30	154.3225.30
M 40 x 1,5	20 - 26	50	37	15	1.610.4000.31	154.4026.30
M 40 x 1,5	22 - 32	50	37	15	1.610.4000.30	154.4032.30
M 50 x 1,5	25 - 31	57	37	15	1.610.5000.31	154.5031.30
M 50 x 1,5	32 - 38	57	37	15	1.610.5000.30	154.5038.30
M 63 x 1,5	29 - 35	68/64	38	15	1.610.6300.31	154.6335.30
M 63 x 1,5	37 - 44	68/64	38	15	1.610.6300.30	154.6344.30
3/8" NPT	2 - 6	19/17	21	15	1.610.3800.71	154.3906.10
3/8" NPT	4 - 8	19/17	21	15	1.610.3800.70	154.3908.10
1/2" NPT	5 - 9	24/22	24	13	1.610.1200.71	154.1909.10
1/2" NPT	6 - 12	24/22	24	13	1.610.1200.70	154.1912.10
3/4" NPT	10 - 16	30	25	13	1.610.3400.71	154.3516.10
3/4" NPT	14 - 18	30	25	13	1.610.3400.70	154.3518.10
1" NPT	13 - 20	40	31	19	1.610.1000.71	154.7520.10
1" NPT	20 - 25	40	31	19	1.610.1000.70	154.7525.10

