

Progress-P / EX

Material: PA, glasfaserverstärkt
 Farbe: grau / schwarz / blau-schwarz
 Dichteinsatz: TPE / NBR *
 Einsatztemperatur: -20°C bis 85°C
 Schutzart: IP 66 / IP 68

Material: PA (nylon), glass-fibre reinforced
 Colour: grey / black / blue-black
 Sealing insert: TPE / NBR *
 Temperature range: -20°C to 85°C
 Protection type: IP 66 / IP 68

Ex e

180.10
180.11
180.14

Zertifikate: SEV 15 ATEX 0152 X
 IECEx SEV 15.0019 X

Certificates: SEV 15 ATEX 0152 X
 IECEx SEV 15.0019 X



Weitere internationale Zulassungen vorhanden

Further international approvals available


* NBR-Dichteinsatz

* NBR-sealing



II 2G Ex eb IIC Gb
 II 2D Ex tb IIIC Db
 II 2G Ex ia IIC Ga
 II 2D Ex ia IIIC Da

Gewinde Entry Thread AG	mm	mm	H mm	GL mm	Progress GFK EX	HUGRO No.
M 16 x 1,5	4,5 - 6	21	26	12	EX15xx.17.060	180.1706.1x
M 16 x 1,5	6 - 8	21	26	12	EX15xx.17.080	180.1708.1x
M 20 x 1,5	6 - 8	27	28	13	EX15xx.20.080	180.2008.1x
M 20 x 1,5	8 - 11	27	28	13	EX15xx.20.110	180.2011.1x
M 25 x 1,5	9,5 - 12,5	34	33	13	EX15xx.25.125	180.2512.1x
M 25 x 1,5	12,5 - 16	34	33	13	EX15xx.25.160	180.2516.1x
M 25 x 1,5	16 - 19	34	33	13	EX15xx.25.190	180.2519.1x
M 25 x 1,5	19 - 20,5	34	33	13	EX15xx.25.205	180.2520.1x
M 32 x 1,5	20 - 21	41	35	15	EX15xx.32.210	180.3221.1x
M 32 x 1,5	21 - 22	41	35	15	EX15xx.32.220	180.3222.1x *
M 32 x 1,5	22 - 23	41	35	15	EX15xx.32.230	180.3223.1x *
M 32 x 1,5	23 - 25,5	41	35	15	EX15xx.32.255	180.3225.1x
M 40 x 1,5	25,5 - 27	50	40	15	EX15xx.40.270	180.4027.1x *
M 40 x 1,5	27 - 28,5	50	40	15	EX15xx.40.285	180.4028.1x
M 40 x 1,5	28,5 - 30	50	40	15	EX15xx.40.300	180.4030.1x *
M 40 x 1,5	30 - 33	50	40	15	EX15xx.40.330	180.4033.1x
M 50 x 1,5	33 - 35	60	42	16	EX15xx.50.350	180.5035.1x *
M 50 x 1,5	35 - 37	60	42	16	EX15xx.50.370	180.5037.1x
M 50 x 1,5	37 - 39	60	42	16	EX15xx.50.390	180.5039.1x *
M 50 x 1,5	39 - 42	60	42	16	EX15xx.50.420	180.5042.1x
M 63 x 1,5	42 - 44	75	48	16	EX15xx.63.440	180.6344.1x *
M 63 x 1,5	44 - 46	75	48	16	EX15xx.63.460	180.6346.1x
M 63 x 1,5	46 - 48	75	48	16	EX15xx.63.480	180.6348.1x *
M 63 x 1,5	48 - 52	75	48	16	EX15xx.63.520	180.6352.1x
Pg 9	4,5 - 6	21	26	12	EX15xx.09.060	180.0906.1x
Pg 9	6 - 8	21	26	12	EX15xx.09.080	180.0908.1x
Pg 11	4 - 5,5	24	28	12	EX15xx.11.055	180.1105.1x
Pg 11	5,5 - 8,5	24	28	12	EX15xx.11.085	180.1108.1x
Pg 13,5	6 - 8	27	28	13	EX15xx.13.080	180.1308.1x
Pg 13,5	8 - 11	27	28	13	EX15xx.13.110	180.1311.1x
Pg 16	6 - 8	27	28	13	EX15xx.16.080	180.1608.1x
Pg 16	8 - 11	27	28	13	EX15xx.16.110	180.1611.1x
Pg 21	9,5 - 12,5	34	33	13	EX15xx.21.125	180.2112.1x
Pg 21	12,5 - 16	34	33	13	EX15xx.21.160	180.2116.1x
Pg 21	16 - 19	34	33	13	EX15xx.21.190	180.2119.1x
Pg 21	19 - 20,5	34	33	13	EX15xx.21.205	180.2120.1x
Pg 29	19,5 - 21	41	36	13	EX15xx.29.210	180.2921.1x *
Pg 29	21 - 23	41	36	13	EX15xx.29.230	180.2923.1x
Pg 29	23 - 25	41	36	13	EX15xx.29.250	180.2925.1x *
Pg 29	25 - 27,5	41	36	13	EX15xx.29.275	180.2927.1x
Pg 36	27 - 28,5	55	42	16	EX15xx.36.285	180.3628.1x *
Pg 36	28,5 - 30,5	55	42	16	EX15xx.36.305	180.3630.1x
Pg 36	30,5 - 32,5	55	42	16	EX15xx.36.325	180.3632.1x *
Pg 36	32,5 - 35	55	42	16	EX15xx.36.350	180.3635.1x
Pg 42	33 - 35	60	42	16	EX15xx.42.350	180.4235.1x *
Pg 42	35 - 37	60	42	16	EX15xx.42.370	180.4237.1x
Pg 42	37 - 39	60	42	16	EX15xx.42.390	180.4239.1x *
Pg 42	39 - 42	60	42	16	EX15xx.42.420	180.4242.1x
Pg 48	41 - 43	70	46	16	EX15xx.48.430	180.4843.1x
Pg 48	43 - 45	70	46	16	EX15xx.48.450	180.4845.1x *
Pg 48	45 - 47	70	46	16	EX15xx.48.470	180.4847.1x *
Pg 48	47 - 49	70	46	16	EX15xx.48.490	180.4849.1x



Bestell-Nummern sind zu ergänzen:		15xx	.1x
Reference numbers have to be completed	grau / grey:	= 1571	= .10
	schwarz / black:	= 1540	= .11
	blau-schwarz / blue-black (Ex i):	= 1530	= .14