

Progress-P / MF-EX

Material: PA glasfaserverstärkt
Farbe: grau RAL 7035 / schwarz RAL 9005
Dichteinsatz: TPE / NBR¹⁾
Einsatztemperatur: -20°C bis 85°C
Schutzart: IP 66 / IP 68

Material: PA (nylon), glass-fibre reinforced
Colours: grey RAL 7035 / black RAL 9005
Sealing insert: TPE / NBR¹⁾
Temperature range: -20°C to 85°C
Protection type: IP 66 / IP 68

Ex e

180.80
180.81


Zertifikate: SEV 15 ATEX 0152 X
IECEX SEV 15.0019 X

Certificates: BVS 14 ATEX E 025 X
IECEX BVS 14.0020 X



II 2G Ex eb IIC Gb
II 2D Ex tb IIIC Db

Gewinde Entry Thread AG				H mm	GL mm	Progress GFK Multi EX	HUGRO No.
M 16 x 1,5	1 - 1,5	4	21	26	12	EX1571.17.4.015	180.17154.80 ¹⁾
M 16 x 1,5	2 - 3	2	21	26	12	EX1571.17.2.030	180.17302.80
M 20 x 1,5	2,5 - 3	6	27	28	13	EX1571.20.6.030	180.20306.80
M 20 x 1,5	3,5 - 5	2	27	27	13	EX1571.20.2.050	180.20502.80
M 25 x 1,5	5 - 6	6	34	33	13	EX1571.25.6.060	180.25606.80
M 25 x 1,5	5,5 - 7	4	34	33	13	EX1571.25.4.070	180.25704.80
M 25 x 1,5	7,5 - 9	3	34	33	13	EX1571.25.3.090	180.25903.80
M 25 x 1,5	8 - 10	2	34	33	13	EX1571.25.2.100	180.25102.80
M 32 x 1,5	6 - 7	6	41	35	15	EX1571.32.6.070	180.32706.80
M 32 x 1,5	7,5 - 9	4	41	35	15	EX1571.32.4.090	180.32904.80
M 40 x 1,5	8 - 9	7	50	40	15	EX1571.40.7.090	180.40907.80 ¹⁾
M 40 x 1,5	14 - 15	2	50	40	15	EX1571.40.2.150	180.40152.81 ¹⁾
M 50 x 1,5	9 - 10	4	60	42	16	EX1571.50.4.100	180.50104.80 ¹⁾
M 63 x 1,5	11 - 12	6	75	48	16	EX1571.63.6.120	180.63126.80 ¹⁾
M 63 x 1,5	17 - 18	3	75	48	16	EX1571.63.3.180	180.63183.80 ¹⁾



schwarz RAL 9005 / black RAL 9005

M 16 x 1,5	1 - 1,5	4	21	26	12	EX1540.17.4.015	180.17154.81 ¹⁾
M 16 x 1,5	2 - 3	2	21	26	12	EX1540.17.2.030	180.17302.81
M 20 x 1,5	2,5 - 3	6	27	28	13	EX1540.20.6.030	180.20306.81
M 20 x 1,5	3,5 - 5	2	27	27	13	EX1540.20.2.050	180.20502.81
M 25 x 1,5	5 - 6	6	34	33	13	EX1540.25.6.060	180.25606.81
M 25 x 1,5	5,5 - 7	4	34	33	13	EX1540.25.4.070	180.25704.81
M 25 x 1,5	7,5 - 9	3	34	33	13	EX1540.25.3.090	180.25903.81
M 25 x 1,5	8 - 10	2	34	33	13	EX1540.25.2.100	180.25102.81
M 32 x 1,5	6 - 7	6	41	35	15	EX1540.32.6.070	180.32706.81
M 32 x 1,5	7,5 - 9	4	41	35	15	EX1540.32.4.090	180.32904.81
M 40 x 1,5	8 - 9	7	50	40	15	EX1540.40.7.090	180.40907.81 ¹⁾
M 40 x 1,5	14 - 15	2	50	40	15	EX1540.40.2.150	180.40152.81 ¹⁾
M 50 x 1,5	9 - 10	4	60	42	16	EX1540.50.4.100	180.50104.81 ¹⁾
M 63 x 1,5	11 - 12	6	75	48	16	EX1540.63.6.120	180.63126.81 ¹⁾
M 63 x 1,5	17 - 18	3	75	48	16	EX1540.63.3.180	180.63183.81 ¹⁾

