

WAZU-EZ

Material: PA + Al
Farbe: schwarz
Dichteinsatz: NBR
O-Ring: NBR
Einsatztemperatur: -20°C bis 70°C
Schutzart: IP 68 - 10 bar / 30 min,
IP 69 K

Material: PA + Al
Colour: black
Sealing insert: NBR
O-ring: NBR
Temperature range: -20°C to 70°C
Protection type: IP 68 - 10 bar / 30 min,
IP 69 K

Ex e

184.EZ

Zertifikate: KEMA 99 ATEX 6971 X
IECEX KEM 07.0014 X



Certificates: KEMA 99 ATEX 6971 X
IECEX KEM 07.0014 X



II 1D Ex ta IIIC Da
II 2G Ex eb IIC Gb

Weitere internationale Zulassungen vorhanden

Further international approvals available

Gewinde Entry Thread AG	 mm	 mm	H mm	GL mm	HSK-K-MZ-Ex	HUGRO No.
M 16 x 1,5	4 - 8	19	29	15	1.215.1601.50	184.1708.EZ
M 20 x 1,5	6 - 12	24	35	15	1.215.2001.50	184.2012.EZ
M 25 x 1,5	13 - 18	33	41	11	1.215.2501.50	184.2518.EZ
M 32 x 1,5	18 - 25	42	49	11	1.215.3201.50	184.3225.EZ
M 40 x 1,5	22 - 32	53	58	13	1.215.4001.50	184.4032.EZ
M 50 x 1,5	32 - 38	60	61	13	1.215.5001.50	184.5038.EZ
M 63 x 1,5	37 - 44	68 / 65	62	14	1.215.6301.50	184.6344.EZ
Pg 9	4 - 8	19	29	15	1.215.0901.14	184.0908.EZ
Pg 11	6 - 10	22	32	15	1.215.1101.14	184.1110.EZ
Pg 13,5	6 - 12	24	35	15	1.215.1301.14	184.1312.EZ
Pg 16	10 - 14	27	37	10	1.215.1601.14	184.1614.EZ
Pg 21	13 - 18	33	41	11	1.215.2101.14	184.2118.EZ
Pg 29	18 - 25	42	49	11	1.215.2901.14	184.2925.EZ
Pg 36	22 - 32	53	58	13	1.215.3601.14	184.3632.EZ
Pg 42	32 - 38	60	61	13	1.215.4201.14	184.4238.EZ
Pg 48	37 - 44	65	62	14	1.215.4801.14	184.4844.EZ

